

DESCRIPTION	STANDARD CONSTRUCTION				OPTION		
	TYPES	C3L	C3S	C3V	C3VF	C3L	C3S
Characteristics	Dwelling module	Sanitary module	Dwelling or sanitary module with exchangeable walls	Dwelling module with exchangeable walls (flat_pack)			
Stackability	2x	2x	2x	2x	3x	3x	
Replaceable walls	NO	NO	YES	YES	YES / C3F		
Transport in packages + storability	NO	NO	NO	YES			
SPECIFICATION							
Dimensions	width	2,438 or 2,990 mm	2,438 or 2,990 mm	2,990 mm	2,990 mm	2,000 mm up to 2,990 mm	
	length	from 2,990 to 6,058 mm	from 2,990 to 6,058 mm	6,058 mm	6,058 mm	Up to 10,000 mm	
	clearance	2,300 or 2,500 mm	2,300 or 2,500 mm	2,500 mm	2,500 mm	Up to 3,000 mm	
	weight	Minimum weight is from 1.2 t to 6 t (weight depends on dimensions and equipment)					
Frame	Welded frame made of galvanized metal sheet						
ROOF							
Roof covering	Galvanized corrugated metal sheet 29 mm, thickness 0.63 mm						
Insulation	Mineral wool, thickness 100 mm					To 220 mm	
Inner ceiling facing	Melaminated chipboard, thickness 10 mm					Plastic, Plasterboard, Wall-paper facing, Lower ceiling	
Water drainage	4 downpipes, Ø60 mm, in internal corners						
Fire resistance	15'		NO		15', 30', 45', 60', 90'		
WALL							
External sheating / coating	Galvanized and coated, slightly corrugated metal sheet of thickness 0.55 mm					Facade systems - ALUbond, Horizontal wave, Facade rendering, Plastic tiling, Flexible brick tiling, Painting in RAL colours	
Painting - surface finish	Coated by two-component acrylic colours (withouth extrapay): RAL 5010, 1013, 9010, 9002, 7035, 7032						
Insulation	Mineral wool, thickness 60 mm		Mineral wool, thickness 80 mm		To 180 mm		
Inner wall facing	Melaminated chipboard, thickness 10 mm					Plastic, Higher level painting, Plasterboard/gypscarton, AL sheets, Ceramic tiles	
Fire resistance	NO		NO		15', 30', 45', 60', 90'		
FLOOR							
Structure	Galvanized steel lattice structure						
Insulation	Mineral wool, thickness 80 mm					To 180 mm	
Floor	Chipboard (V100) - thick. 22 mm, or (extrapay) Fibre cement board (CETRIS) - thick. 22 mm	Sanitary module	Fibre cement board (CETRIS) - thick. 22 mm	Fibre cement board (CETRIS) - thick. 22 mm			
Floor covering	PVC Tarkett Standard 184; grey - thick. 1.5 mm	PVC Tarkett Standard 184; grey - thick. 1.5 mm or floated continuous floor Marathopact type	PVC Tarkett Standard 184; grey - thick. 1.5 mm	PVC Tarkett Standard 184; grey - thick. 1.5 mm	Ceramic tiles, Carpets of various types, Other by customer's needs		
ELECTROINSTALLATION							
Installation	In walls and ceiling		In walls, ceiling and cover strips				
Inlet / outlet	400 V / 32 A					up to 400 V / 63A	
Lights	2pcs fluorescent lights 1 x 36 W with cover		4pcs fluorescent lights 1 x 36 W with cover			By customer's needs	
Accessories	3x socks, 1x switch					By customer's needs	
Electric switchboard	1 x 10A; 2 x 16A; FI 25 A					By customer's needs	
EQUIPMENT							
External door	ZK type of door, size 875 x 2000 mm, insulated, made of painted metal sheet, incl hardware and cylindrical lock plug					By customer's needs	
Inner door	Wooden foaliated door (with honeycomb pane)		ZK type of door (metal sheet, galvanized) or wooden foaliated door (with honeycomb pane)			By customer's needs	
Window	Window size 1765 x 1335 mm, in plastic frame, open/tilting, integrated outer plastic blind, double glazed, Ug=1.1	Window size 600 x 450 mm in plastic frame, tilting, double glazed, Ug=1.1	Window size 1765 x 1335 mm, in plastic frame, open/tilting, integrated outer plastic blind, double glazed, Ug=1.1	Window size 1765x1335 mm, in plastic frame, open/tilting, integrated outer plastic blind, double glazed, Ug=1.1	By customer's needs		
Sanitary equipment	NO	YES (acc.to type)	NO	NO	By customer's needs		